

A short list of the most useful R commands

A summary of the most important commands with minimal examples. See the relevant part of the [guide](#) for better examples. For all of these commands, using the `help(function)` or `? function` is the most useful source of information. Unfortunately, knowing what to ask for help about is the hardest problem.

See the [R-reference card](#) by Tom Short for a much more complete list.

Input and display

```

read.table(filename,header=TRUE)           #read files with labels in first row
read.table(filename,header=TRUE,sep=',')    #read a tab or space delimited file
read.csv(filename)                        #read csv files

x=c(1,2,4,8,16)                         #create a data vector with specified elements
y=c(1:10)                                #create a data vector with elements 1-10
n=10

x1=c(rnorm(n))                          #create a n item vector of random normal deviates
y1=c(runif(n))+n                         #create another n item vector that has n added to each random uniform distribution
z=rbinom(n,size,prob)                    #create n samples of size "size" with probability prob from the binomial
vect=c(x,y)                            #combine them into one vector of length 2n
mat=cbind(x,y)                          #combine them into a n x 2 matrix
mat[4,2]                                #display the 4th row and the 2nd column
mat[,1]                                 #display the 3rd row
mat[,2]                                 #display the 2nd column
subset(dataset,logical)                 #those objects meeting a logical criterion
subset(data.df,select=variables,logical) #get those objects from a data frame that meet a criterion
data.df[data.df==logical]               #yet another way to get a subset
x[order(x$B)]                           #sort a dataframe by the order of the elements in B
x[rev(order(x$B))]                      #sort the dataframe in reverse order

browse.workspace                         #a menu command that creates a window with information about all variables in

```

moving around

```

ls()                                     #list the variables in the workspace
rm(x)                                    #remove x from the workspace
rm(list=ls())                            #remove all the variables from the workspace
attach(mat)                             #make the names of the variables in the matrix or data frame available in the workspace
detach(mat)                            #releases the names
new=old[,n]                            #drop the nth column
new=old[,n]                            #drop the nth row
new=subset(old,logical)                 #select those cases that meet the logical condition
complete = subset(data.df,complete.cases(data.df)) #find those cases with no missing values
new=old[n1:n2,n3:n4]                     #select the n1 through n2 rows of variables n3 through n4

```

distributions

```

beta(a, b) gamma(x) choose(n, k) factorial(x) dnorm(x, mean=0, sd=1, log = FALSE) #normal distribution pnorm(q, mean=0, sd=1, lower.tail = TRUE, log.p = FALSE) qnorm(p, mean=0, sd=1, lower.tail = TRUE, log.p = FALSE) rnorm(n, mean=0, sd=1) dunif(x, min=0, max=1, log = FALSE) #uniform distribution punif(q, min=0, max=1, lower.tail = TRUE, log.p = FALSE) runif(n, min=0, max=1)

```

data manipulation

```

replace(x, list, values)                #remember to assign this to some object i.e., x <- replace(x,x==9,NA)
                                         #similar to the operation x[x==9] <- NA

cut(x, breaks, labels = NULL,
     include.lowest = FALSE, right = TRUE, dig.lab = 3, ...)

x.df=data.frame(x1,x2,x3 ...)          #combine different kinds of data into a data frame
as.data.frame()
is.data.frame()

x/as.matrix()                           #converts a data frame to standardized scores
scale()

round(x,n)                            #rounds the values of x to n decimal places
ceiling(x)                            #vector x of smallest integers > x
floor(x)                             #vector x of largest integer < x
as.integer(x)                         #truncates real x to integers (compare to round(x,0))
as.integer(x < cutpoint)              #vector x of 0 if less than cutpoint, 1 if greater than cutpoint)
factor(ifelse(a < cutpoint, "Neg", "Pos")) #is another way to dichotomize and to make a factor for analysis
transform(data.df,variable.names = some.operation) #can be part of a set up for a data set

x%in%y                                #tests each element of x for membership in y
y%in%x                                #tests each element of y for membership in x
all(x%in%y)                            #true if x is a proper subset of y
all(x)                                 # for a vector of logical values, are they all true?
any(x)                                 #for a vector of logical values, is at least one true?

```

Statistics and transformations

```

max()
min()
mean()
median()
sum()
var()      #produces the variance covariance matrix
sd()       #standard deviation
mad()      #(median absolute deviation)
fivenum()  #Tukey fivenumbers min, lowerhinge, median, upper hinge, max
table()    #frequency counts of entries, ideally the entries are factors(although it works with integers or even reals)
scale(data,scale=T) #centers around the mean and scales by the sd)
cumsum(x)  #cumulative sum, etc.
cumprod(x)
cummax(x)
cummin(x)
rev(x)     #reverse the order of values in x

cor(x,y,use="pair")  #correlation matrix for pairwise complete data, use="complete" for complete cases
aov(x~y,data=datafile) #where x and y can be matrices
aov.ex1 = aov(DV~IV,data=data.ex1) #do the analysis of variance or
aov.ex2 = aov(DV~IV1*IV2,data=data.ex2)      #do a two way analysis of variance

```

```

summary(aov.ex1)                      #show the summary table
print(model.tables(aov.ex1,"means"),digits=3)    #report the means and the number of subjects/cell
boxplot(DV~IV,data=data.ex1)          #graphical summary appears in graphics window

lm(x~y,data=dataset)                 #basic linear model where x and y can be matrices (see plot.lm for plotting options)
t.test(x,g)
pairwise.t.test(x,g)
power.anova.test(groups = NULL, n = NULL, between.var = NULL,
                  within.var = NULL, sig.level = 0.05, power = NULL)
power.t.test(n = NULL, delta = NULL, sd = 1, sig.level = 0.05,
             power = NULL, type = c("two.sample", "one.sample", "paired"),
             alternative = c("two.sided", "one.sided"), strict = FALSE)

```

More statistics: Regression and Linear model

```

lm(Y~X)                                #Y and X can be matrices
lm(Y~X1+X2)
lm(Y~X)[W]
solve(A,B)                             #inverse of A * B - used for linear regression
solve(A)                               #inverse of A
factanal()
princomp()

```

Useful additional commands

```

colSums (x, na.rm = FALSE, dims = 1)
rowSums (x, na.rm = FALSE, dims = 1)
colMeans(x, na.rm = FALSE, dims = 1)
rowMeans(x, na.rm = FALSE, dims = 1)
rowsum(x, group, reorder = TRUE, ...)
apply(X, MARGIN, FUN, ...)
  apply(x,1,min)
  apply(x,2,max)
col.max(x)
which.min(x)
which.max(x)
z=apply(big5r,1,which.min)           #tells the row with the minimum value for every column

```

Graphics

```

par(mfrow=c(nrow,mcol))                #number of rows and columns to graph
par(ask=TRUE)                          #ask for user input before drawing a new graph
par(omi=c(0,0,1,0) )                  #set the size of the outer margins
mtext("some global title",3,outer=TRUE,line=1,cex=1.5)   #note that we seem to need to add the global title last
  #cex = character expansion factor

boxplot(x,main="title")               #boxplot (box and whiskers)

title( "some title")                  #add a title to the first graph

hist()                                 #histogram
plot()                                

  plot(x,y,xlim=range(-1,1),ylim=range(-1,1),main=title)
  par(mfrow=c(1,1))                   #change the graph window back to one figure
  symb=c(19,25,3,23)
  colors=c("black","red","green","blue")
  charact=c("S","T","N","H")
  plot(PA,NAF,pch=symb[group],col=colors[group],bg=colors[condit],cex=1.5,main="Positive vs. Negative Affect by Film condition")
  points(mPA,mNA,pch=symb[condit],cex=4.5,col=colors[condit],bg=colors[condit])

curve()
abline(a,b)
  abline(a, b, untf = FALSE, ...)
  abline(h=, untf = FALSE, ...)
  abline(v=, untf = FALSE, ...)
  abline(coef=, untf = FALSE, ...)
  abline(reg=, untf = FALSE, ...)

identify()
  plot(eatar,eanta,xlim=range(-1,1),ylim=range(-1,1),main=title)
  identify(eatar,eanta,labels=labels(energysR[,1]))      #dynamically puts names on the plots
locate()

legend()
pairs()                                #SPLOM (scatter plot Matrix)
pairs.panels ()                         #SPLOM on lower off diagonal, histograms on diagonal, correlations on diagonal
  #not standard R, but uses a function found in useful.r
matplot ()
biplot ())
plot(table(x))                         #plot the frequencies of levels in x

x= recordPlot()                        #save the current plot device output in the object x
replayPlot(x)
dev.control                            #replot object x
  #various control functions for printing/saving graphic files
pdf(height=6, width=6)                #create a pdf file for output
dev.of()
layout(mat)                           #close the pdf file created with pdf
  #specify where multiple graphs go on the page
  #experiment with the magic code from Paul Murrell to do fancy graphic location

layout(rbind(c(1, 1, 2, 2, 3, 3),
             c(0, 4, 4, 5, 5, 0)))
for (i in 1:5) {
  plot(i, type="n")
  text(1, i, paste("Plot", i), cex=4)
}

```

Distributions

To generate random samples from a variety of distributions

```

runif(n,lower,upper)
rnorm(n,mean,sd)
rbinom(n,size,p)
sample(x, size, replace = FALSE, prob = NULL)      #samples with or without replacement

```

Working with Dates

```
date <-strptime(as.character(date), "%m/%d/%y") #change the date field to a internal form for time  
#see ?formats and ?POSIXlt  
as.Date  
month<- months(date) #see also weekdays, Julian
```

[Additional functions](#) that I have created because I needed some specific operation may be included in the workspace by issuing the source command:

```
source(http://personality-project.org/r/useful.r)
```

These functions include:

```
#alpha.scale      #find coefficient alpha for a scale and a datafram of items  
#describe        give means, sd, skew, n, and se  
#summ.stats      #basic summary statistics by a grouping variable  
#error.crosses   (error bars in two space)  
#skew            find skew  
#panel.cor       taken from the examples for pairs  
#pairs.panels    adapted from panel.cor -- gives a splom, histogram, and correlation matrix  
#multi.hist      #plot multiple histograms  
#correct.cor     #given a correlation matrix and a vector of reliabilities, correct for reliability  
#fisherz          #convert pearson r to fisher z  
#paired.r         #test for difference of dependent correlations  
#count.pairwise  #count the number of good cases when doing pairwise analysis  
#eigen.loadings  #convert eigen vector vectors to factor loadings by unnormalizing them  
#principal       #yet another way to do a principal components analysis -- brute force eigenvalue decomp  
#factor.congruence #find the factor congruence coefficints  
#factor.model    #given a factor model, find the correlation matrix  
#factor.residuals #how well does it fit?  
#factor.rotate   # rotate two columns of a factor matrix by theta (in degrees)  
#phi2poly        #convert a matrix of phi coefficients to polychoric correlations
```

part of a [short guide to R](#)
Version of February 20, 2005
[William Revelle](#)
[Department of Psychology](#)
[Northwestern University](#)